

AD-F20

Heavy Duty Floor Stripper

TECHNICAL DATA SHEET

Description

An economical floor stripper, AD-F20 is a powerful, non-ammoniated butyl-based formula that cuts through heavy build-up and hard to remove water-based sealers in record time.

Directions

1. Mix stripper with cold water per the following dilutions: Heavy coating removal: 32) 1:4 US oz per gallon/250 ml per 1 liter of water). Normal coating removal: 21.5) 1:6 US oz per gallon/166 ml per 1 liter of water). Light coating removal: 16) 1:8 US oz per gallon / 125 ml per 1 liter of water).
2. Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
3. Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
4. Rinse thoroughly with clean water and allow floor to dry completely before applying any finish.

Note: Test floor for color fastness in an inconspicuous area.

Technical Data

Description	Non-ammoniated, ultra high performance stripper
Appearance	Clear red liquid
Viscosity (Brookfield) @ 68F (°20C)	<5 centipoise
Flash Point ASTM D2010) 05-56)	158°F (70°C)
VOC 40 CFR Part 59 Subpart C	%33 (as supplied)
Fragrance	Slight lemon
Shelf Life ASTM D2008) 93-1791)	2 years
Density ASTM D2008) 98-1475)	8.3 lb/gal @ 68F 0.99 kg/L @ 20C
Container	1.06 US gal/4 L

