

AD-F2

Dry Bright Floor Coating

TECHNICAL DATA SHEET

Description

AD-F2 is an excellent, low maintenance coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbings.

Directions


Read all directions and Safety Data Sheets (SDS) before using.

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 5-6 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats.
2. Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 4 coats of finish.
3. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats.

Technical Data

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (°60) ASTM D2008) 87-1455)	>85
Viscosity (Brookfield) @ °68F (°20C)	<10 centipoise
Coverage Rate	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	About 30 minutes
Removability ASTM D06-1792	Excellent
VOC 40 CFR Part 59 Subpart C	0.01%
Non-Volatile Solids ASTM D2008) 95-2834)	20%

Fragrance	Slight ammoniacal
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D2008) 93-1791)	1 year
Density ASTM D2008) 98-1475)	8.6 lb/gal @ °68F 1.03 kg/L @ °20C
Detergent Resistance ASTM D2008) 92-3207)	Excellent
Freeze/Thaw ASTM D2008) 93-3209)	Passes 3 cycles
Container	1.06 US gal/4 L



Floor Coating and Finishing materials
as to slip resistance only.

42E6



ADVANCE
HYGIENE